

SPECIFICATIONS

LUMINA

ECOLITE

OUTLITE

STREET LIGHTING

Model	Lumina 7	Lumina 9	Lumina 11	Lumina 18	Ecolite 8	Ecolite 18	Outlite	SLB18PL	SLB36PL	SLB18SX	SLB26SX
Lamp Wattage	7 W	9 W	11 W	18 W	8 W	18 W	18 W	18 W	36 W	18 W	26 W
Nominal Voltage	12 or 24 VDC	12 or 24 VDC	12 or 24 VDC	12, 24, 48 VDC	12 or 24 VDC	12 or 24 VDC	12, 24, 48 VDC	12, 24, 48 VDC	12 or 24 VDC	12 or 24 VDC	12 or 24 VDC
Current Consumption at 12V	0.5 A	0.6 A	0.89 A	1.3 A	0.75 A	1.3 A	1.3 A	1.3 A	2.5 A	1.5 A	2.3 A
Current Consumption at 24V	0.25 A	0.3 A	0.45 A	0.65 A	0.37 A	0.65 A	0.65 A	0.65 A	1.25 A	0.75 A	1.15 A
Current Consumption at 48V	N/A	N/A	N/A	0.33 A	N/A	N/A	0.33 A	0.33 A	N/A	N/A	N/A
Type of Tube	Compact Fluorescent	Compact Fluorescent	Compact Fluorescent	Compact Fluorescent	Straight Fluorescent	Straight Fluorescent	Compact Fluorescent	Compact Fluorescent	Compact Fluorescent	Sodium SOX-E	Sodium SOX-E
Tube Lumen Output	400	600	900	1200	410	1150	1200	1200	2800	1800	3700
Colour of Light Emitted	White	White	White	White	White	White	White	White	White	Yellow	Yellow
Inverter Frequency (KHz)	>30 KHz	>30 KHz	>30 KHz	>30 KHz	>30 KHz	>30 KHz	>30 KHz	>30 KHz	>30 KHz	>30 KHz	>30 KHz
Inverter Waveform	Pure Sinewave	Pure Sinewave	Pure Sinewave	Pure Sinewave	Pure Sinewave	Pure Sinewave	Pure Sinewave	Pure Sinewave	Pure Sinewave	Pure Sinewave	Pure Sinewave
Inverter Efficiency	>90%	>90%	>90%	>90%	>90%	>90%	>90%	>90%	>90%	>90%	>90%
Operating Temperature Range	-10 to +50°C	-10 to +50°C	-10 to +50°C	-10 to +50°C	-10 to +50°C	-10 to +50°C	-10 to +50°C	-10 to +50°C	-10 to +50°C	-10 to +50°C	-10 to +50°C
Open Circuit Protected	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Short Circuit Protected	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Reverse Polarity Protected	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Optional Switch	Push Switch	Push Switch	Push Switch	Push Switch	Rocker Switch	Pull Cord	N/A	N/A	N/A	N/A	N/A
Warranty Period*	Two Years	Two Years	Two Years	Two Years	Two Years	Two Years	Two Years	Two Years	Two Years	Two Years	Two Years
Packaging	Full colour retail carton	Full colour retail carton	Full colour retail carton	Full colour retail carton	Plain Carton	Protective Wrap	Plain Carton	Plain Carton	Plain Carton	Plain Carton	Plain Carton
Packed Dimensions (mm)	350x80x50	350x80x50	350x80x50	350x80x50	440x90x40	675x75x40	260x140x130	420x160x170	420x160x170	420x160x170	420x160x170
Packed Weight (Kg)	0.3	0.3	0.3	0.3	0.32	0.6	0.9	2	2	2	2
Order Multiple	50	50	50	50	100	50	10	2	2	2	2
Replacement Lamp Specifications <i>CFLs are 4 pin</i>	Sollatek 68507806 Philips 7PLS84 Osram DSE784 GE F7BX/840 Sylvania SE7W/840	Sollatek 68509807 Philips 9PLS84 Osram DSE984	Sollatek 68511808 Philips 11PLS84 Osram DSE1184	Sollatek 68518602 Philips 18PLL84 Osram DL1884 GE F11BX/840 Sylvania L18W/840	Sollatek 68708802 Philips TL833 Osram L820 GE F18BX/840 Sylvania F8W/133	Sollatek 68718802 Philips TLD1833 Osram L1820 GE F8W/33 Sylvania F18W/133	Sollatek 68518604 Philips 18PLC84 Osram DDE 184 GE F18W/33 Sylvania DE18W/840	Sollatek 68518602 Philips 18PLL84 Osram DL1884 GE F18DBX/840 Sylvania L18W/840	Sollatek 68536802 Osram DF3684 Sylvania F36W/840 GE F18BX1840	Sollatek 68518610 Philips 18SOXE Osram SXE26	Sollatek 68526610 Philips 26S OXE Osram SXE26 GE SOX26E

* excludes lamp

**2 YEARS
WORLDWIDE
WARRANTY**

**ON ALL SOLLATEK
PRODUCTS**



SOLLATEK (UK) LTD


UNIT 10 POYLE 14 INDUSTRIAL ESTATE, NEWLANDS DRIVE, POYLE, SLOUGH SL3 0DX, UNITED KINGDOM.

Tel: International +44 1753 688300 National 01753 688300
Fax: International +44 1753 685306 National 01753 685306

E-mail: sales@sollatek.com

www.sollatek.com

All weights and dimensions are approximate. Specifications are subject to change without prior notice. SOL14 June 04.



Ecolite 18

www.sollatek.com



©Sollatek (UK) Limited 1996 All Rights Reserved.

SOLLATEK and the SOLLATEK SOLAR device are the trade marks of the Sollatek group of companies.

SOLAR LIGHTING PRODUCTS

SOLLATEK SOLAR designs, manufactures and supports a wide variety of solar related products.

Whilst being one of the world's largest suppliers of OEM products, the company also has extensive expertise in designing and producing bespoke solar systems which are currently being utilised worldwide.

LUMINA

LUMINA

- High efficiency Compact Fluorescent Lamps (4 pin)
- Available in 7, 9, 11 and 18 watt versions
- 12, 24 or 48 volt DC versions
- Low Current Consumption
- Optional Switch



ECOLITE

ECOLITE

- Linear Fluorescent Tube
- Available in 8 or 18 watt versions
- 12 or 24 volt DC versions
- Low current consumption
- Optional Switch



OUTLITE

OUTLITE

- High Efficiency Compact Fluorescent Lamp - 18W
- Available in 12, 24 or 48 Volt DC versions
- Vandal resistant Polycarbonate construction
- Weatherproof to IP65
- Low current consumption



STREET LIGHTING

STREET LIGHTING

- IP65, Weatherproof bulkhead (GRP)
- 18 and 36 watt fluorescent, 18 and 26 watt low pressure sodium (SOX-E)
- 12 or 24 or 48 volt DC versions
- Inverter / ballasts are tropicalised
- Side entry 35mm spigot

